

## 1.View and size(视图及尺寸)

### Main technical indicators(主要技术指标)

|                                 |                                                                                                                    |
|---------------------------------|--------------------------------------------------------------------------------------------------------------------|
| 1.Mating (插拔次数)                 | 5000                                                                                                               |
| 2.Working Temperature (温度)      | -55~+150 ℃                                                                                                         |
| 3.IP Rating (防护级别)              | IP 50                                                                                                              |
| 4.Diameter of socket end(插头端直径) | φ1.3                                                                                                               |
| 5.Testing Voltage (测试电压)        | 1300V                                                                                                              |
| 6.Working Voltage (工作电压)        | 1550V                                                                                                              |
| 7.Rated Current (额定电流)          | 12A                                                                                                                |
| 8.Shell material(壳体材质)          | Brass (chromium plating) shell and chuck nut/( nickel plating) pin sleeve and middleware/黄铜(镀铬)外壳和夹头螺母/(镀镍)插销套和中间件 |
| 9.Pin Material(插针材料)            | Copper alloy gold plating(铜合金镀金)                                                                                   |
| 10.Insulator material(绝缘体材质)    | PPS                                                                                                                |


### Sum up(总结)

|                             |                                      |
|-----------------------------|--------------------------------------|
| Series(系列)                  | B                                    |
| Shell style/model (外壳样式/型号) | THG: Elbow plug, cable collet/电缆夹头弯头 |
| Button (按键)                 | A button(一个按键)                       |
| Termination type (终止类型)     | Male solder(公焊锡)                     |
| Line diameter awg(线材直径)     | 28-20AWG                             |
| Cable diameterφ (电缆直径)      | φ5.3-6.2MM                           |
| Matching parts(配件)          | ZGG.1B.P03.CLL                       |


### Location pin combination(定位销组合)

| (编号)<br>Number | Number of<br>positioning pins(定<br>位销数量) | Angle(<br>角度) | Series(系列)-1B              |
|----------------|------------------------------------------|---------------|----------------------------|
| G              | One(1)                                   |               | (Zero degrees)0°           |
| A              | Two(2)                                   | A             | Thirty degrees(30°)        |
| B              | Two(2)                                   |               | Sixty degrees(60°)         |
| C              | Two(2)                                   |               | Ninety degrees(90°)        |
| D              | Two(2)                                   | β             | 135 degrees(135°)          |
| E              | Two(2)                                   |               | 145 degrees(145°)          |
| F              | Two(2)                                   |               | 155 degrees(155°)          |
| J              | Two(2)                                   | Y             | Forty-five<br>degrees(45°) |
| K              | Two(2)                                   |               | Seventy degrees(70°)       |
| L              | Two(2)                                   |               | 80 degrees(80°)            |


|        | A      | B      | C√     | ANGLE   |       |
|--------|--------|--------|--------|---------|-------|
| 5-10   | ±0.02  | ±0.05  | ±0.1   | 0°-30°  | ±0.1° |
| 50-100 | ±0.1   | ±0.15  | ±0.2   | 61°-90° | ±0.5° |
| 50-100 | ±0.15  | ±0.2   | ±0.25  |         |       |
| 100-   | ±0.15% | ±0.20% | ±0.25% |         |       |




|    | A      | D     | H      | L      | M      | S1     | S2     | S3     |
|----|--------|-------|--------|--------|--------|--------|--------|--------|
| MM | 13.5   | 8     | 29.5   | 36.0   | 25     | 11     | 9      | 10     |
| in | 0.5315 | 0.315 | 1.1614 | 1.4173 | 0.9843 | 0.4331 | 0.3543 | 0.3937 |



Welded surface  
(焊接面)



Positive view  
(正视图)



Solder core  
(焊接型胶胶芯)

TH G. 1B. P03.C L A D 62 H

Model(型号)

Positioning pin(定位销)

Series(系列)

Needle core configuration(针芯配置)

Outer casing(外壳)

Insulator(绝缘体)

Needle core(针芯)

Type of clamp(线夹类型)

Cable diameter(电缆直径)

SH means a sheath type, not a cover type.

(H表示护套型, 不表示为不带护套型)

|                                  |          |                                      |          |                                         |
|----------------------------------|----------|--------------------------------------|----------|-----------------------------------------|
| DESIGNED (设计)                    | DATE(日期) | SCALE(比例)                            | N/A(不适用) | MODEL TYPE<br>型号类型: THG.1B.P03.CLAD.62H |
| CHECKED (校对)                     | DATE(日期) | VIEW(视图)                             |          | PART NO. 1B3-core plug<br>名称: 1B3芯插头    |
| APPROVED (审核)                    | DATE(日期) | UNIT(单位)                             | MM       | DWG NO.:                                |
| REVISIONS                        |          | MATERIAL (材料)                        |          | WEIGHT(重量) SHEET(表) REVISION(修订)        |
| www.helloxkb.com www.helloxkb.cn |          | XKB INDUSTRIAL PRECISION CO.,LIMITED |          | 1/1 A0                                  |